

COMMON RAIL CALIBRATION THICKNESS KIT

CALIBRATION THICKNESS KITS: to modify the pression of the calibration, start pression and the quantity of fuel of the common rail injector. Reducing the thickness we obtain an increase in the opening pression (Bar), of the start pression (Bar) and in the quantity of fuel (Cm³) of the injector.

AZ0019-08CR



Diam : 5,50 mm.
Hole : 3,40 mm.
Thickness : 1,20 - 1,70 mm. (24 measures)

Cut: each 0.02 mm.
Box : 10 items x thickness
Total : 240 items

AZ0019-08CR5 **NEW**



Diam : 5,50 mm.
Hole : 3,40 mm.
Thickness : 1,20 - 1,70 mm. (11 measures)

Cut: each 0.05 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-17CR **NEW**



Diam : 5,50 mm.
Hole : 3,40 mm.
Thickness : 0,90 - 1,90 mm. (21 measures)

Cut: each 0.05 mm.
Box : 10 items x thickness
Total : 210 items

AZ0019-12CR **NEW**



Diam : 4,50 mm.
Hole : 2,00 mm.
Thickness : 1,20 - 1,70 mm. (24 measures)

Cut: each 0.02 mm.
Box : 10 items x thickness
Total : 240 items

AZ0019-12CR5



Diam : 4,50 mm.
Hole : 2,00 mm.
Thickness : 1,20 - 1,70 mm. (11 measures)

Cut: each 0.05 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-14CR



Diam : 4,20 mm.
Hole : 2,00 mm.
Thickness : 1,20 - 1,70 mm. (24 measures)

Cut: each 0.02 mm.
Box : 10 items x thickness
Total : 240 items

AZ0019-14CR5 **NEW**



Diam : 4,20 mm.
Hole : 2,00 mm.
Thickness : 1,20 - 1,70 mm. (11 measures)

Cut: each 0.05 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-15CR **NEW**



Diam : 5,30 mm.
Hole : 2,40 mm.
Thickness : 1,20 - 1,70 mm. (24 measures)

Cut: each 0.02 mm.
Box : 10 items x thickness
Total : 240 items

AZ0019-21CR



Diam : 5,30 mm.
Hole : 2,40 mm.
Thickness : 1,72 - 1,90 mm. (10 measures)

Cut: each 0.02 mm.
Box : 10 items x thickness
Total : 110 items

diesel levante

SOLENOID WASHERS KIT: useful to modify the solenoid power. Reducing/increasing the thickness of the washer the solenoid power reduces/raises.

AZ0019-11CR



Diam : 23,50 mm.
Hole : 19,00 mm.
Thickness : 1,00 – 1,10 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-18CR

NEW



Diam : 23,50 mm.
Hole : 19,00 mm.
Thickness : 0,90 – 1,00 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-10CR



Hex : 22,00 mm.
Hole : 19,00 mm.
Thickness : 1,00 – 1,10 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-19CR

NEW



Hex : 22,00 mm.
Hole : 19,00 mm.
Thickness : 0,90 – 1,00 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

SETTLEMENT WASHERS KIT: useful to modify the conjunction between the upper lever of the ball-holder and the smooth part of the holding-ball valve. It enables the regulation of the solenoid and so the movement of the ball.

AZ0019-09CR



Diam : 15,70 mm.
Hole : 10,50 mm.
Thickness : 1,20 – 1,30 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

KIT OF POINTERS: to modify the fuel quantity of the common rail injectors. Reducing the thickness of the pointers we obtain an increase in the fuel quantity of the injector.

AZ0019-07CR



Diam : 5,90 mm.
Thickness : 8,40 – 8,50 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-13CR



Diam : 5,80 mm.
Thickness : 8,40 – 8,50 mm. (11 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 110 items

AZ0019-22CR

NEW



Diam : 5,80 mm.
Thickness : 8,50 – 8,70 mm. (21 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 210 items

AZ0019-20CR



Diam : 2,25 mm.
Thickness : 1,14 – 1,25 mm. (12 measures)

Cut: each 0.01 mm.
Box : 10 items x thickness
Total : 120 items